



P218

Roving for Spray-up

PRODUCT DESCRIPTION

P218 is a multi-end roving produced using Advantex® glass fiber. Advantex® glass fiber combines the electrical and mechanical properties of traditional E-glass with the acid corrosion resistance of E-CR glass.

This Advantex® Glass Roving has a sizing system with a silane coupling agent. It has been designed to provide optimal performance for spray-up applications.



PRODUCT REFERENCE

Example : EC 2400 P218
E : glass type
C : continuous process
2400 : roving linear weight (tex)
P218 : OCV™ Reinforcements product classification code

FEATURES AND PRODUCT BENEFITS

- Easy rolling and air release

TECHNICAL CHARACTERISTICS (NOMINAL VALUES)

LINEAR WEIGHT (TEX)	LOSS ON IGNITION (%)	MOISTURE (%)
ISO 1889: 1997	ISO 1887: 1995	ISO 3344: 1997
2400	1.0% +/- 0.15	≤ 0.15

P218

Roving for Spray-up

PACKAGING

- Each P218 cheese is protected by a shrink-wrap polythene film and identified by an individual label. Please do not remove film during use.

Product	Pallet Dimensions L x W (cm)	Layers per pallet	Cheeses per layers	Total number of cheeses	PALLETS	
					Approx. height (cm)	Net weight* (kg)
P218	114 x 114	4	16	64	119	1300

(*) Add 35 to 45 kg to obtain gross weight.

STORAGE

The P218 roving should be stored in its original packaging in a dry and cool place. Best conditions are at temperature from 10 to 35°C and humidity between 35 and 85%. If you store the product at lower temperatures, please move the soon-to-be-processed pallets to the production area 24 hours ahead of time. You can stock pallets one on one with a plywood plank between the two.



OCV™ Reinforcements

OWENS CORNING

COMPOSITE MATERIALS, LLC

ONE OWENS CORNING PARKWAY

TOLEDO, OHIO 43659

1.800.GET.PINK™

www.owenscorning.com

www.ocvreinforcements.com

Contact:

MultiEndRovings.ocvamericas@owenscorning.com

OWENS CORNING

FIBERGLAS, SPRL.

166, CHAUSSÉE DE LA HULPE

B-1170 BRUSSELS

BELGIUM

+32.2.674.82.99

Contact:

MultiEndRovings.ocvemea@owenscorning.com

OWENS CORNING - OCV ASIA PACIFIC

SHANGHAI REGIONAL HEADQUARTERS

2F OLIVE LVO MANSION

620 HUA SHAN ROAD

SHANGHAI 200040

CHINA

+86.21.62489922

Contact:

MultiEndRovings.ocvap@owenscorning.com

This information and data contained herein is offered solely as a guide in the selection of a reinforcement. The information contained in this publication is based on actual laboratory data and field test experience. We believe this information to be reliable, but do not guarantee its applicability to the user's process or assume any responsibility or liability arising out of its use or performance. The user agrees to be responsible for thoroughly testing any application to determine its suitability before committing to production. It is important for the user to determine the properties of its own commercial compounds when using this or any other reinforcement. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose. Statements in this publication shall not be construed as representations or warranties or as inducements to infringe any patent or violate any law safety code or insurance regulation.